

## SET UP INSTRUCTIONS

### 3345 TWO TIER FLOWER NYMPH FOUNTAIN

### 3440 TWO TIER LARGE GRECIAN LADY FOUNTAIN

Open bag containing the pump kit **P95003**. In the kit you will find:

1 - 02720 (950 gallon per hour pump)	2 - 1/2" plastic ell	2 - restrictor
1 - 53" long piece of 1/2" clear tubing	1 - 3/4" plastic tee	1 - tube of silicone
1 - 15" long piece of 3/4" clear tubing	1 - 3/4" plastic ell	2 - hose clamp
1 - 22" long piece of 1" clear tubing	1 - 1/2" plastic tee	1 - rubber stopper

1. Place pedestal on a firm surface where fountain will remain and level. Level in (2) Two directions left to right and front to back. Shim as needed. Place the largest shell on the pedestal.
2. Attach one end of 1" clear tubing 22" long to outlet of pump with a hose clamp. Place pump in pump house in center of shell and run the plug end of the electrical cord down the PVC pipe in the pump house and down through the pedestal. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust the position of the rubber stopper on the power cord if necessary.
3. Position the largest shell on pedestal and level. To level shell, place level on top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. Shim as needed.
4. Run the 1" clear tubing through the center hole in spacer. Place spacer on top of pumphouse in center of shell and level as stated in step #3.
5. Take the second shell and run the 1" clear tubing up thru the PVC insert in the center housing of the shell. **Make Sure the 1" Clear Tubing Does Not Kink or Get Sandwiched Between Shells** while shell is being positioned on spacer. Trim the 1" clear tubing 6" above the floor inside the center housing of the second shell.
6. Find the piece of 3/4" clear tubing 15" long and cut one piece 9" long, one piece 3 1/2" long and one piece 1 1/2" long. Find the piece of 1/2" clear tubing 53" long and cut two pieces 23" long, two pieces 2" long and one piece 1" long. Find 1/2" plastic tee. On both ends of the 1/2" plastic tee attach a piece of 1/2" clear tubing 2" long. Find two 1/2" plastic elbows and attach one on each end of the 1/2" plastic tee. On the opposite ends of the two 1/2" plastic elbows attach a piece of 1/2" clear tubing 23" long with a white plastic restrictor clamp on both. On the middle connection of the 1/2" plastic tee slip on a piece of 1/2" clear tubing 1" long all the way. Then on the same middle connection attach the piece of 3/4" clear tubing 3 1/2" long with a hose clamp. Find the 3/4" plastic tee and attach an end connection to the opposite end of the 3/4" clear tubing 3 1/2" long. Attach the piece of 3/4" clear tubing 9" long onto the opposite end connection of the 3/4" plastic tee. Find the 3/4" plastic ell and attach it to the opposite end of the 3/4" clear tubing 9" long. Attach the piece of 3/4" clear tubing 1 1/2" long onto the middle connection of the 3/4" plastic tee.

#### **THE TUBING KIT FOR THIS FOUNTAIN IS ALREADY ASSEMBLED FOR YOU Except for adjusting the length of the clear tubing do not modify this tubing kit.**

7. Attach the middle connection of the 3/4" plastic tee onto the end of the 1" clear tubing located in the center housing of the second shell. Place the 3/4" clear tubing connected to the 3/4" plastic ell in the groove located in the wall of the center housing of the second shell. The 3/4" plastic ell will be on the outside of the center housing. Point the 3/4" plastic ell down.
8. Place spacer on top of center housing and level as stated in step #3. In the center hole of the spacer you will see the two 1/2" clear tubing connections for the statue hook up. At this time adjust the two restrictor clamps. Close both white plastic restrictor clamp 4 clicks.
9. Remove any excess concrete or tape from both ends of copper pipes in statue. Place statue on top of fountain. Tilt statue and attach the two pieces of 1/2" clear tubing with white plastic restrictor clamps to the two connections on the bottom of the LARGE GRECIAN LADY or to the FLOWER NYMPH.
10. Fill shells with tap water and plug pump into a 110 vac GFCI protected outlet.
11. If fountain needs adjustment, unplug pump and adjust the two white plastic restrictor clamps to regulate water flow of the statue until the desired result is achieved.