

SET UP INSTRUCTIONS

3586 62" GABRIEL LION HEAD FOUNTAIN ON POOL

3681 64" GABRIEL LION HEAD FOUNTAIN ON POOL

Open bag containing the pump kit **P51502**. In the kit you will find:

1 - 02617 (515 gallon per hour pump) 1 - rubber stopper 1 - putty tape
1 - 52" long piece of 3/4" clear tubing

1. Place the pool on a firm level surface where fountain will remain. Place a brick under one side of pool. This will help you retrieve the power cord from under the pool.
2. Find the pump, 3/4" clear tubing 52" long and the rubber stopper. Attach one end of 3/4" clear tubing 52" long to the outlet side of the pump. Place pump in pump house in center of pool and run the plug end of the electrical cord down the PVC pipe located in the pump house and out the bottom of the pool. Retrieve cord from under pool and place in groove in bottom of pool. Remove brick from under pedestal. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust position of the rubber stopper on the power cord if necessary.
3. To level pool, place level on top rim of the pump house in the center of pool. Level in (2) Two directions left to right and front to back. **Shim as needed.**
4. Find the larger shell and run the 3/4" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the large shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.
5. Find the small shell. On a padded surface lay the small shell up side down. On the bottom of the small shell you will see a PVC pipe. Clean any excess concrete or tape from around and inside this PVC pipe. Run the 3/4" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the larger shell and level. To level shell, place level on the top rim of the shell. Level as stated in step #3.
6. Before you trim the 3/4" clear tubing to length push the 3/4" clear tubing down so the pump will be resting on the floor of the pool. Trim the 3/4" clear tubing to 12" above the floor inside the cavity of the small shell.
Find the piece putty tape and remove the backing. Apply the putty tape around the 3/4" clear tubing where the tubing passes through the shell inside the cavity.
7. Find the finial. On the bottom of the finial you will see a PVC pipe. Clean any excess concrete or tape from both ends and inside of this PVC pipe. Slip the finial onto the 3/4" clear tubing and position the finial on the fountain.
8. Find the drain plugs and insert them snugly into the drain insert located in the pool and the larger shell. Remove any tape and or dirt from the drain insert before you insert the drain plug. Fill the pool and shells with water and plug pump into a 110VAC GFCI protected outlet.