



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS **3601 TWO TIER PARLOR FOUNTAIN**

(THIS FOUNTAIN IS HEAVY; YOU WILL NEED HELP WITH SETUP).

Open bag containing the pump kit **P29020**. In the kit you will find:

- 1 - KING 400 (400 gallon per hour pump)
- 1 - rubber stopper
- 1 - 42" long piece of 3/4" clear tubing

1. Place the pedestal base on a firm level surface where fountain will remain. To level the pedestal base, place level on top surface of the pedestal base. Level in (2) Two directions left to right and front to back. **Shim as needed.** There is a large groove in the bottom of the pedestal base. To help you retrieve the power cord of the pump run a piece of rope or wire about 6 feet long in the groove into the center hole of the pedestal base. Place the pedestal on the pedestal base and level. Retrieve the rope or wire up through the hole in the pedestal.

2. Find the pump. Move the large shell onto a padded surface close to the pedestal base. Place the pump into the pump house located in center of the large shell and run the plug end of the power cord down the PVC pipe located in the pump house. Tilt shell and retrieve the cord from under the shell. Attach the rope or wire to the plug end of the power cord and carefully pull the opposite end of the rope or wire until the power cord is thru the groove in pedestal base. Make sure you have enough slack in the power cord so that the pump will sit on the bottom surface of the pump house.

3. Position the large shell on pedestal and level. To level shell, place level on top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. **Shim as needed.**

4. Find the rubber stopper and the piece of 3/4" clear tubing 42" long. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Adjust position of the rubber stopper on the power cord if necessary. Attach one end of the 3/4" clear tubing onto the outlet side of the pump.

5. Find the second shell and make sure the hole running through the center is clear. Place a piece of padding on the pump house located in the center of the large shell. Place the second shell on the pump house running the 3/4" clear tubing up thru the center hole of the shell. Remove padding. Position this shell on top of the large shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.

6. Find the finial and remove any excess concrete or tape from inside and both ends of the PVC pipe located in the center of the finial. Before placing the finial on the fountain. Cut the 3/4" clear tubing 10" above the top surface of the center housing on the second shell. Slide the finial onto the 3/4" clear tubing. Position the finial on top of fountain.

7. Find the drain plug and insert it snugly into the drain insert located in the large shell. Remove any tape and or dirt from inside the drain insert before you insert the drain plug. Fill shells with water and plug pump into a 110VAC GFCI protected outlet.

3888sup 6/17/11