



# MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

## SET UP INSTRUCTIONS 3637 CATALINA FOUNTAIN

Open bag containing the pump kit **P22503**. In the kit you will find:

- |   |                      |
|---|----------------------|
| 1 - 40225 (225 gallon per hour pump)    | 1 - rubber stopper   |
| 1 - 27" long piece of 3/4" clear tubing | 1 - tube of silicone |

1. Place the pool on a firm and level surface where fountain will remain. Place a brick under one side of pool. This will help when you retrieve the power cord from under the pool.
2. Find the pump, the 3/4" clear tubing 27" long, and the rubber stopper. Place the pump in the pump house located in the center of the pool and run the plug end of the electrical cord down the PVC pipe in the pump house. Retrieve cord from under the pool and place in groove in the bottom of the pool. Leave enough slack in the power cord so the pump will rest on the bottom of the pumphouse. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust the position of the rubber stopper on the power cord if necessary. Remove the brick.
3. To level the pool, place the level on pump house located in the center of the pool. Level in (2) Two directions left to right and front to back. Shim as needed.
4. Find the tall shell finial and on a padded surface lay it on its side. In the bottom of the tall shell finial there is a PVC pipe. Remove any tape and or dirt from the PVC pipe. Attach the 3/4" clear tubing to the pump. With the pump resting on the bottom of the pumphouse measure up from the top surface of the pumphouse and cut the 3/4" clear tubing at 23 1/2". Insert the 3/4" clear tubing into the PVC pipe that is in the bottom of the tall shell finial until the 3/4" clear tubing is almost even with the opposite end of the PVC pipe. Position the tall shell finial centered on top of the pumphouse located in the center of the pool. After the tall finial is positioned on the pumphouses of the pool. Push the 3/4" clear tubing back down the PVC pipe until the pump is resting on the bottom on the pumphouse. To level place the level on the top rim of the tall shell finial. Level in (2) Two directions left to right and front to back. Shim as needed.
5. Find the drain plug and insert them snugly into the drain insert located in both the pool and the shell. Remove any tape and or dirt from the drain insert before you insert the drain plug. Fill the pool and the shell with tap water and plug pump into a 110VAC GFCI protected outlet. To adjust the water flow to the finial use the dial type flow control located on the front of the pump until the desired result is achieved.

3637sup      6/2/10