



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3666 67" VICENZA FOUNTAIN

Open bag containing the pump kit **P29018**. In the kit you will find:

1 – KING 400 (400 gallon per hour pump)	1 - rubber stopper	1 – hose clamp
1 – tube of silicone	1 - 36" long piece of 3/4" clear tubing	

1. Place the pedestal on a firm and level surface where fountain will remain. Place the large shell on the pedestal.
2. Find the pump, the rubber stopper, the 3/4" clear tubing 36" long and the hose clamp. Place the pump in the pumphouse located in the center of the shell and run the plug end of the electrical cord down the PVC pipe in the pump house and down through the pedestal. Retrieve cord from under pedestal and place in groove in the bottom of the pedestal. Leave enough slack in the power cord so the pump will rest on the bottom of the pumphouse. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pumphouse. Adjust the position of the rubber stopper on the power cord if necessary. Attach the piece of 3/4" clear tubing 36" long onto the outlet side of the pump with the hose clamp.
3. Position the large shell on top of the pedestal and level. To level shell, place the level on the pumphouse located in the center of the shell. Level in (2) Two directions left to right and front to back. Shim as needed.
4. Find the spacer and run the 3/4" clear tubing up thru the center hole and position the spacer on top of the pumphouse located in center of largest shell. Level as stated in step #3.
5. Find the second shell and run the 3/4" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell centered on top of the pumphouse located in center of largest shell. Level as stated in step #3.
6. Before you trim the 3/4" clear tubing to length. Push the 3/4" clear tubing back down until the pump is resting on the bottom on the pumphouse. Cut the length of the 3/4" clear tubing to 11" above the center surface of the second shell.
7. Find the finial. Slip the finial onto the 3/4" clear tubing located in the center of the second shell. Position the finial on the fountain.
8. Fill shells with tap water and plug pump into a 110VAC GFCI protected outlet. To adjust the water flow to the finial, unplug the pump and remove the finial from the fountain. Trim the 3/4" clear tubing another 1/2" shorter and reposition the finial on the fountain. If necessary repeat by cutting the 3/4" clear tubing another 1/2" shorter. This will regulate water flow from the finial until the desired result is achieved. Keep the pieces of the 3/4" clear tubing that you have cut. If you happen to cut the 3/4" clear tubing too short you can insert the cut piece back in the finial. Insert the cut piece of 3/4" clear tubing into the PVC pipe located in the center of the finial and push the piece down into the PVC pipe as far as it will go.

3666sup 7/1/09