



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3736 – PICCOLO RUSCELLO FOUNTAIN

3742 – ALBERO FOUNTAIN

Open the bag containing the pump kit **P13017**. In the kit you will find:

- | | | |
|--|---------------------------|---------------------------|
| 1 - 40160 (160 gallon per hour pump) | 1 – 2-hole rubber stopper | 1 - hose clamp |
| 1 – 2" long piece of 1/2" clear tubing | 1 – #3 stopper with hole | 1 – LED light kit (white) |
| 1 – 8" long piece of 1/2" kink free tubing | | |

Run the LED power cord through the PVC insert in the finial first.

1. Find the fountain bowl, the finial, the pump and the LED light kit. Place the fountain bowl on a firm and level area where the fountain will remain. On a padded surface **CAREFULLY** place the finial near the fountain bowl. In the top, of the finial there is a PVC insert. Run the plug end and the quick thread nut on the LED light power cord down the PVC insert and out the bottom of the finial. Pull the remainder of the LED light power cord out the bottom of the finial. Find the smaller stopper with the single hole and slip it onto the power cord of the LED light about 3 1/2" from the LED light head. Insert the smaller rubber stopper snugly into the PVC insert. Find the piece of 1/2" clear tubing 2" long and connect it to the 1/2" connection on the LED light head. Connect the opposite end of the 1/2" clear tubing to the copper pipe located in the top of the finial.
2. Find the 1/2" kink free tubing 8" long and the hose clamp. Attach the 1/2" kink free tubing to the outlet side of the pump with the hose clamp.
3. Find the 2-hole rubber stopper. Slip the 2-hole rubber stopper onto the power cord of the pump and the power cord of the LED light. Position the 2-hole rubber stopper about 8" from the body of the pump and on the LED power cord about 10" from the bottom of the finial.
4. Located in the pump house in the center of the fountain bowl there is a PVC pipe. Run the plug end of both power cords, the pump and the LED light, down the PVC pipe and out the bottom of the fountain bowl. Insert the 2-hole rubber stopper snugly into the PVC pipe. Place the finial on the pump house that is located in the center of the fountain bowl. Retrieve both power cords from under the fountain base and place both in the groove in the bottom of the fountain bowl.
5. Connect the opposite end of the 1/2" kink free tubing to the copper pipe located in the bottom of the finial. Position the finial on the fountain and level.
6. Find the drain plug and insert snugly into the drain insert located in the fountain bowl. Remove any tape and or dirt from inside the drain insert before you insert the drain plug. Fill the fountain bowl with water.
7. Connect the power cord on the LED light to the transformer. Plug both the pump and the LED light transformer into a 110VAC GFCI protected outlet. Adjust the water flow using the built in flow control dial on the front of the pump.

3858sup

6/28/12